

# Thermal Single Ecoflex

## Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

## Données techniques

Material	PEX
Subcomponent Material	Material Jacket: Corrugated seamless high-density polyethylene (HDPE); UV-protected
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

## Informations sur le produit et utilisation de l'application

Uponor's Ecoflex® Thermal Single is a pre-insulated pipe for buried or aboveground commercial and residential hydronic heating and cooling applications. Service pipes are made from durable Engel-method crosslinked polyethylene (PEX-a) tubing with multilayer PEX-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use with ProPEX® Fittings or WIPEX™ dezincification-resistant (DZR) brass compression fittings.1



Nom de la pièce	Numéro de pièce	Inner diameter coil [inch]	Outer diameter coil [inch]	Coil width [inch]	Inner diameter pipe [inch]	Outer diameter pipe [inch]	R value	Weight per UOM [lbs/UOM]
3/4" Thermal Single with 2.7" Jacket, 1,000-ft. coil	5012775	2.7	12	2.7	0.671	0.875	9.3	0.35
1" Thermal Single with 2.7" Jacket, 1,000-ft. coil	5012710	2.7	12	2.7	0.862	1.125	7.4	0.38
1" Thermal Single with 5.5" Jacket, 600-ft. coil	5015510	5.5	12	5.5	0.862	1.125	12.3	0.75
1 1/4" Thermal Single with 5.5" Jacket, 500-ft. coil	5015513	5.5	12	5.5	1.054	1.375	10.7	0.85
1 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil	5016915	6.9	12	6.9	1.244	1.625	10.8	1.4
2" Thermal Single with 6.9" Jacket, 300-ft. coil	5016920	6.9	12	6.9	1.629	2.125	8.9	1.8
2 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil	5016925	6.9	12	6.9	2.011	2.625	7.2	1.97
3" Thermal Single with 7.9" Jacket, 300-ft. coil	5017930	7.9	12	7.9	2.398	3.125	7	2.8
3 1/2" Thermal Single with 7.9" Jacket, 300-ft. coil	5017935	7.9	12	7.9	2.784	3.625	-	2.98
4" Thermal Single with 7.9" Jacket, 300-ft. coil	5017940	7.9	12	7.9	3.169	4.125	4.8	3.7

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Thermal Single Ecoflex	All	UPC IPC NPC of Canada UMC NSPC IMC	ASTM F1960	cNSFus-rfh cNSFus-pw U.P.Code
In addition, the following parts have additional codes, standards, or listings:				
3/4" Thermal Single with 2.7" Jacket, 1,000-ft. coil	5012775		CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14	
1" Thermal Single with 2.7" Jacket, 1,000-ft. coil	5012710		ASTM F877 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14	
1" Thermal Single with 5.5" Jacket, 600-ft. coil	5015510		ASTM F877 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14	
1 1/4" Thermal Single with 5.5" Jacket, 500-ft. coil	5015513		ASTM F877 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14	
1 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil	5016915		ASTM F877 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14	
2" Thermal Single with 6.9" Jacket, 300-ft. coil	5016920		ASTM F877 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14	
2 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil	5016925		ASTM F877 CSA B137.5 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14	
3" Thermal Single with 7.9" Jacket, 300-ft. coil	5017930		ASTM F877 CSA B137.5 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14	
3 1/2" Thermal Single with 7.9" Jacket, 300-ft. coil	5017935		ASTM F877 CSA B137.5 ASTM F876 NSF-61 ASTM F876 NSF-14	
4" Thermal Single with 7.9" Jacket, 300-ft. coil	5017940		ASTM F877 CSA B137.5 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14	

#### L'installation

Install Ecoflex Thermal Single pre-insulated pipe in buried or aboveground hydronic heating and cooling applications. Use Uponor ProPEX or WIPEX DZR brass compression fittings. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For more information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.

#### Applications connexes

Pre-Insulated Pipe Systems  
Hydronic Heating and Cooling Systems  
Radiant Heating and Cooling Systems  
Permafrost Prevention Systems  
Turf Conditioning Systems

#### Notes de bas de page

#### Coordonnées de la personne-ressource

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517