

Thermal Single Ecoflex

Renseignements sur le projet

| | |
|-----------------------------|---------------------|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |

Données techniques

| | |
|-----------------------|---|
| Material | PEX |
| Subcomponent Material | Material Jacket: Corrugated seamless high-density polyethylene (HDPE); UV-protected |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) |
| | 180 °F (82 °C) at 100 psi (6.9 bar) |
| | 200 °F (93 °C) at 80 psi (5.5 bar) |

Informations sur le produit et utilisation de l'application

Uponor's Ecoflex® Thermal Single is a pre-insulated pipe for buried or aboveground commercial and residential hydronic heating and cooling applications. Service pipes are made from durable Engel-method crosslinked polyethylene (PEX-a) tubing with multilayer PEX-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use with ProPEX® Fittings or WIPEX™ dezincification-resistant (DZR) brass compression fittings.1



| Nom de la pièce | Numéro de pièce | Inner diameter coil [inch] | Outer diameter coil [inch] | Coil width [inch] | Inner diameter pipe [inch] | Outer diameter pipe [inch] | R value | Weight per UOM [lbs/UOM] |
|--|-----------------|----------------------------|----------------------------|-------------------|----------------------------|----------------------------|---------|--------------------------|
| 3/4" Thermal Single with 2.7" Jacket, 1,000-ft. coil | 5012775 | 2.7 | 12 | 2.7 | 0.671 | 0.875 | 9.3 | 0.35 |
| 1" Thermal Single with 2.7" Jacket, 1,000-ft. coil | 5012710 | 2.7 | 12 | 2.7 | 0.862 | 1.125 | 7.4 | 0.38 |
| 1" Thermal Single with 5.5" Jacket, 600-ft. coil | 5015510 | 5.5 | 12 | 5.5 | 0.862 | 1.125 | 12.3 | 0.75 |
| 1 1/4" Thermal Single with 5.5" Jacket, 500-ft. coil | 5015513 | 5.5 | 12 | 5.5 | 1.054 | 1.375 | 10.7 | 0.85 |
| 1 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil | 5016915 | 6.9 | 12 | 6.9 | 1.244 | 1.625 | 10.8 | 1.4 |
| 2" Thermal Single with 6.9" Jacket, 300-ft. coil | 5016920 | 6.9 | 12 | 6.9 | 1.629 | 2.125 | 8.9 | 1.8 |
| 2 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil | 5016925 | 6.9 | 12 | 6.9 | 2.011 | 2.625 | 7.2 | 1.97 |
| 3" Thermal Single with 7.9" Jacket, 300-ft. coil | 5017930 | 7.9 | 12 | 7.9 | 2.398 | 3.125 | 7 | 2.8 |
| 3 1/2" Thermal Single with 7.9" Jacket, 300-ft. coil | 5017935 | 7.9 | 12 | 7.9 | 2.784 | 3.625 | - | 2.98 |
| 4" Thermal Single with 7.9" Jacket, 300-ft. coil | 5017940 | 7.9 | 12 | 7.9 | 3.169 | 4.125 | 4.8 | 3.7 |

| Nom de la pièce | Numéro de pièce | Les codes | Normes | Annonces |
|---|-----------------|---------------------------------------|--|-------------------------------|
| Thermal Single Ecoflex | All | UPC IPC NPC of Canada UMC NSPC IMC | ASTM F1960 | cNSFus-rfh cNSFus-pw U.P.Code |
| In addition, the following parts have additional codes, standards, or listings: | | | | |
| 3/4" Thermal Single with 2.7" Jacket, 1,000-ft. coil | 5012775 | | CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14 | |
| 1" Thermal Single with 2.7" Jacket, 1,000-ft. coil | 5012710 | | ASTM F877 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 | |
| 1" Thermal Single with 5.5" Jacket, 600-ft. coil | 5015510 | | ASTM F877 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 | |
| 1 1/4" Thermal Single with 5.5" Jacket, 500-ft. coil | 5015513 | | ASTM F877 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 | |
| 1 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil | 5016915 | | ASTM F877 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 | |
| 2" Thermal Single with 6.9" Jacket, 300-ft. coil | 5016920 | | ASTM F877 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 | |
| 2 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil | 5016925 | | ASTM F877 CSA B137.5 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 | |
| 3" Thermal Single with 7.9" Jacket, 300-ft. coil | 5017930 | | ASTM F877 CSA B137.5 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 | |
| 3 1/2" Thermal Single with 7.9" Jacket, 300-ft. coil | 5017935 | | ASTM F877 CSA B137.5 ASTM F876 NSF-61 ASTM F876 NSF-14 | |
| 4" Thermal Single with 7.9" Jacket, 300-ft. coil | 5017940 | | ASTM F877 CSA B137.5 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 | |

L'installation

Install Ecoflex Thermal Single pre-insulated pipe in buried or aboveground hydronic heating and cooling applications. Use Uponor ProPEX or WIPEX DZR brass compression fittings. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For more information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.

Applications connexes

Pre-Insulated Pipe Systems
Hydronic Heating and Cooling Systems
Radiant Heating and Cooling Systems
Permafrost Prevention Systems
Turf Conditioning Systems

Notes de bas de page

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517