

Tuyaux d'eau potable à double paroi Ecoflex en PEX

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	PEX
Subcomponent Material	Jacket: Corrugated, seamless high-density polyethylene (HDPE); UV-protected
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)



Informations sur le produit et utilisation de l'application

Ecoflex® Potable PEX Twin features two Uponor AquaPEX® service pipes protected by multilayer PEX-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use Ecoflex Potable PEX Twin for hot and cold potablewater applications. Join pipes using Uponor ProPEX® or WIPEXTM fittings.1

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

Nom de la pièce	Numéro de pièce	Inner diameter coil [inch]	Outer diameter coil [inch]	Coil width [inch]	Inner diameter pipe [inch]	Outer diameter pipe [inch]	R value	Weight per UOM [lbs/UOM]
1" Potable PEX Twin with 6.9" Jacket, 600-ft. coil	5226910	6.9	12	6.9	0.862	1.125	11.3	1.3
1 1/4" Potable PEX Twin with 6.9" Jacket, 500-ft. coil	5226913	6.9	12	6.9	1.054	1.375	9.5	1.4
1 1/2" Potable PEX Twin with 6.9" Jacket, 300-ft. coil	5226915	6.9	12	6.9	1.244	1.625	7.7	1.55
2" Potable PEX Twin with 7.9" Jacket, 300-ft. coil	5227920	7.9	12	7.9	1.629	2.125	6.5	2.68

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annexes
Tuyaux d'eau potable à double paroi Ecoflex en PEX	All	UPC IPC NPC of Canada NSPC	ASTM F1960 CSA B137.5 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 ASTM F2023 ASTM F877	U.P.Code

L'installation

Install Ecoflex Potable PEX in hot or cold potable-water applications. Join pipes using Uponor ProPEX®. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For additional information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.

Applications connexes

- Pre-Insulated Pipe Systems
- Permafrost Prevention Systems
- Plumbing Systems
- AquaSAFE™ Fire Safety Systems

Notes de bas de page

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517