

Adaptateurs et raccords droits filetés pour collecteur en laiton



Renseignements sur le projet


Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

End type 1	ISO 228-G 1-1/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Informations sur le produit et utilisation de l'application

Uponor's Threaded Brass Manifold Bushings are used in TruFLOW™ manifolds. In radiant heating applications, the bushing transitions the R32 manifold union nut to 1" national pipe thread (NPT) and 3/4" threaded connections (PEX or Multi-layer Composite (MLC) tubing with QS-style fittings).



Nom de la pièce	Numéro de pièce	A [inch]	B [inch]	C [inch]	D [inch]	Material group	End Type 2	E [inch]	F [inch]	G [inch]	H [inch]
Threaded Brass Manifold Straight Adapter, R32 Male x R20 Male	A4143220	0.635	0.35	0.599	2.02	Brass	ISO 228-G 3/4"	1.584	1.75	1.01	0.875
Threaded Brass Manifold Straight Adapter, R32 Male x R25 Male	A4143225	0.613	0.35	0.635	2.02	LF Brass	ISO 228-G 1"	1.598	1.75	1.01	0.875
Threaded Brass Manifold Bushing, R32 Male x 3/4" Female NPT	A2133275	2.018	1.75	0.985	-	Brass	FNPT 3/4"	-	-	-	-
Threaded Brass Manifold Bushing, R32 Male x 1" Female NPT	A2123210	1.918	1.687	0.985	-	Brass	FNPT 1"	-	-	-	-

Nom de la pièce	Numéro de pièce	Weight per UOM [lbs/UOM]
Threaded Brass Manifold Straight Adapter, R32 Male x R20 Male	A4143220	0.55
Threaded Brass Manifold Straight Adapter, R32 Male x R25 Male	A4143225	0.5
Threaded Brass Manifold Bushing, R32 Male x 3/4" Female NPT	A2133275	0.44
Threaded Brass Manifold Bushing, R32 Male x 1" Female NPT	A2123210	0.3

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Adaptateurs et raccords droits filetés pour collecteur en laiton	All	IMC IRC NBC of Canada UMC	CSA B137.5 R32: ISO 228-G 1 1/4" ASTM F877	cNSFus-rfh

L'installation

Thread directly into Uponor TruFLOW manifolds. For additional information, refer to the TruFLOW Manifold Instruction Sheet or the Uponor Radiant Floor Heating Installation Handbook.

Applications connexes

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Notes de bas de page

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517