

Commande de fonte des neiges par zone

Renseignements sur le projet

| | |
|-----------------------------|---------------------|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |

Données techniques

| | |
|---|-----|
| Ambient temperature min. [F] | °f |
| Ambient temperature max. [F] | °f |
| Ambient humidity non-condensing max [%] | 90 |
| Prop 65 label required? | Yes |

Informations sur le produit et utilisation de l'application

The Uponor Single-zone Snow Melt Control is designed to operate electric or hydronic equipment to melt snow or ice. The control has an automatic start and stop function when used with the Uponor Pavement Snow and Ice Sensor (A3040090) or Uponor Aerial Snow Sensor (A3040095). The control can be configured to operate a modulating hydronic boiler or a mixing device and features boiler protection, an idle function and warm/cold weather lockout. Accessories include a Pavement Snow and Ice Sensor (A3040090), a Pavement Snow and Ice Sensor Cup (A3040091), an Aerial Snow Sensor (A3040095) and a Slab Sensor for Aerial Snow Sensor (A3040073).



| Nom de la pièce | Numéro de pièce | Relay rating at 24VAC [A] | Weight per UOM [lbs/UOM] |
|-------------------------------|-----------------|---------------------------|--------------------------|
| Single-zone Snow Melt Control | A3040654 | 2 | - |

| Nom de la pièce | Numéro de pièce | Les codes | Normes | Annonces |
|---------------------------------------|-----------------|-----------|-----------------|----------|
| Commande de fonte des neiges par zone | A3040654 | - | Class II wiring | - |

| L'installation | Applications connexes |
|--|---|
| Fasten terminal connectors on the Single-zone Snow Melt Control. Refer to the Uponor Single-zone Snow Melt Control Installation and Operation Manual for more information. | <ul style="list-style-type: none"> Radiant Heating and Cooling Systems Permafrost Protection Systems Turf Conditioning Systems |

Remarques :

Power consumption:
 16 VA standby 100 VA full load
 Relay rating at 24VAC [A] :
 3.6 combined
 Modulating output:
 0-10 (dc) 500 ohm load impedance
 4-20 mA 1k max load impedance
 Sensors:
 NTC thermistor, 10

| Notes de bas de page | Coordonnées de la personne-ressource | |
|----------------------|---|---|
| - | Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 | Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517 |