

Adaptateurs et raccords droits filetés pour collecteur en laiton



Renseignements sur le projet


| | |
|-----------------------------|---------------------|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |

Données techniques

| | |
|-------------------------|--|
| End type 1 | ISO 228-G 1-1/4" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |

Informations sur le produit et utilisation de l'application

Uponor's Threaded Brass Manifold Bushings are used in TruFLOW™ manifolds. In radiant heating applications, the bushing transitions the R32 manifold union nut to 1" national pipe thread (NPT) and 3/4" threaded connections (PEX or Multi-layer Composite (MLC) tubing with QS-style fittings).



| Nom de la pièce | Numéro de pièce | A [inch] | B [inch] | C [inch] | D [inch] | Material group | End Type 2 | E [inch] | F [inch] | G [inch] | H [inch] |
|---|-----------------|----------|----------|----------|----------|----------------|----------------|----------|----------|----------|----------|
| Threaded Brass Manifold Straight Adapter, R32 Male x R20 Male | A4143220 | 0.635 | 0.35 | 0.599 | 2.02 | Brass | ISO 228-G 3/4" | 1.584 | 1.75 | 1.01 | 0.875 |
| Threaded Brass Manifold Straight Adapter, R32 Male x R25 Male | A4143225 | 0.613 | 0.35 | 0.635 | 2.02 | LF Brass | ISO 228-G 1" | 1.598 | 1.75 | 1.01 | 0.875 |
| Threaded Brass Manifold Bushing, R32 Male x 3/4" Female NPT | A2133275 | 2.018 | 1.75 | 0.985 | - | Brass | FNPT 3/4" | - | - | - | - |
| Threaded Brass Manifold Bushing, R32 Male x 1" Female NPT | A2123210 | 1.918 | 1.687 | 0.985 | - | Brass | FNPT 1" | - | - | - | - |

| Nom de la pièce | Numéro de pièce | Weight per UOM [lbs/UOM] |
|---|-----------------|--------------------------|
| Threaded Brass Manifold Straight Adapter, R32 Male x R20 Male | A4143220 | 0.55 |
| Threaded Brass Manifold Straight Adapter, R32 Male x R25 Male | A4143225 | 0.5 |
| Threaded Brass Manifold Bushing, R32 Male x 3/4" Female NPT | A2133275 | 0.44 |
| Threaded Brass Manifold Bushing, R32 Male x 1" Female NPT | A2123210 | 0.3 |

| Nom de la pièce | Numéro de pièce | Les codes | Normes | Annonces |
|--|-----------------|---------------------------|--|------------|
| Adaptateurs et raccords droits filetés pour collecteur en laiton | All | IMC IRC NBC of Canada UMC | CSA B137.5 R32: ISO 228-G 1 1/4" ASTM F877 | cNSFus-rfh |

L'installation

Thread directly into Uponor TruFLOW manifolds. For additional information, refer to the TruFLOW Manifold Instruction Sheet or the Uponor Radiant Floor Heating Installation Handbook.

Applications connexes

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Notes de bas de page

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517