

# Pinces à tube

## Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

## Données techniques

Material Plastic  
 Subcomponent Material Polypropylene (PP)

## Informations sur le produit et utilisation de l'application

Tube Clamps secure 1/2" and 3/4" Uponor crosslinked polyethylene (PEX-a) tubing products.



Nom de la pièce	Numéro de pièce	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
Tube Clamp Suspension (1/2 PEX), 100/pkg.	A7250500	2	1.407	0.75	0.01
Tube Clamp Suspension (3/4 PEX), 50/pkg.	A7250750	2	1.672	0.75	0.01
Tube Clamp Standard (1/2 PEX), 100/pkg.	A7350500	2	0.86	0.687	0.02
Tube Clamp Standard (3/4 PEX), 50/pkg.	A7350750	2.375	1.125	0.687	0.02

L'installation	Applications connexes
Fasten the tube clamp onto the tubing mounting surface. Refer to the Uponor Radiant Floor Installation Handbook or the Uponor Professional Plumbing Installation Guide for additional information	Radiant Heating and Cooling Systems
	Permafrost Protection Systems
	Turf Conditioning Systems
	PEX-a Plumbing Systems
	AquaSAFE™ Fire Safety Systems

Notes de bas de page	Coordonnées de la personne-ressource
-	<p>Uponor Inc.            5925 148th Street West            Apple Valley, MN 55124            T 800.321.4739            F 952.891.2008</p> <p>Uponor Ltd.            6510 Kennedy Road            Mississauga, ON L5T 2X4            T 888.594.7726            F 800.638.9517</p>