

Crochets pour tube

Renseignements sur le projet


| | |
|-----------------------------|---------------------|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |

Données techniques

Material Plastic

Informations sur le produit et utilisation de l'application

Tube Talon secures 3/8", 1/2", 5/8", 3/4" and 1" Uponor crosslinked polyethylene (PEX) tubing products. Fasteners are included.



| Nom de la pièce | Numéro de pièce | A [inch] | B [inch] | C [inch] | Subcomponent Material | Weight per UOM [lbs/UOM] |
|---|-----------------|----------|----------|----------|----------------------------------|--------------------------|
| Tube Talon (3/8" PEX), 100/pkg. | F7050375 | 1.575 | 0.957 | 0.354 | Polypropylene (PP) | 0.01 |
| Tube Talon (1/2", 5/8", 3/4" PEX), 100/pkg. | F7050750 | 2.217 | 1.551 | 0.4 | High-density polyethylene (HDPE) | 0.01 |
| Tube Talon (1" PEX), 50/pkg. | F7051000 | 2.806 | 1.622 | 0.535 | Polypropylene (PP) | 0.02 |

L'installation

Mount the tube talon over the tubing and mounting surface. Attach the tube talon to desired surface with the nail provided. Refer to the Uponor Radiant Floor Installation Handbook or the Uponor Professional Plumbing Installation Guide for additional information.

Applications connexes

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems
- PEX-a Plumbing Systems

Notes de bas de page

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517