

## Heliopex X2

### Renseignements sur le projet

|                             |                     |
|-----------------------------|---------------------|
| Nom du poste :              | Lieu :              |
| Ingénieur :                 | Date de soumission: |
| Entrepreneur :              | Présentée par:      |
| Représentant du fabricant : | Approuvé par :      |

### Données techniques

|                       |  |
|-----------------------|--|
| Material              | PEX  |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar)<br>180 °F (82 °C) at 100 psi (6.9 bar)<br>200 °F (93 °C) at 80 psi (5.5 bar) |

### Informations sur le produit et utilisation de l'application

Manufactured using an Uponor-proprietary technology, Uponor helioPEX™ X2 is an oxygen-barrier PEX pipe that meets DIN 4726 and is designed as a competitive alternative for residential radiant heating applications. The pipe features exceptional workability, flexibility, and kink reparability and is backed by a 25-year limited warranty. Uponor helioPEX™ X2 is rated and listed by the Hydrostatic Stress Board of PPI at 93.3°C (200°F) at 80 psi, 82.2°C (180°F) at 100 psi, and 23°C (73.4°F) at 160 psi. The product offering is available in ½", ¾", or 1" coils and is compatible with ProPEX® ASTM F1960 expansion, ASTM F2080 compression, and ASTM F1807 crimp fittings.

**Note:** Uponor helioPEX X2 is not approved for potable-water applications.



| Nom de la pièce                         | Numéro de pièce | Inner diameter coil [inch] | Outer diameter coil [inch] | Coil width [inch] | Inner diameter pipe [inch] | Outer diameter pipe [inch] | Weight per UOM [lbs/UOM] |
|---|-----------------|----------------------------|----------------------------|-------------------|----------------------------|----------------------------|--------------------------|
| 1/2" Uponor helioPEX X2, 500-ft. coil   | H1240500        | 15.75                      | 32                         | 6.5               | 0.475                      | 0.625                      | 28.75                    |
| 1/2" Uponor helioPEX X2, 1,000-ft. coil | H1220500        | 15.75                      | 32                         | 10.5              | 0.475                      | 0.625                      | 57.5                     |
| 5/8" Uponor helioPEX X2, 400-ft. coil   | H1210625        | 15.75                      | 32                         | 6.5               | 0.574                      | 0.75                       | 35                       |
| 5/8" Uponor helioPEX X2, 1,000-ft. coil | H1220625        | 15.75                      | 32                         | 16                | 0.574                      | 0.75                       | 86                       |
| 3/4" Uponor helioPEX X2, 300-ft. coil   | H1250750        | 22                         | 32                         | 8                 | 0.671                      | 0.875                      | 30.2                     |
| 3/4" Uponor helioPEX X2, 500-ft. coil   | H1240750        | 15.75                      | 32                         | 10.5              | 0.671                      | 0.875                      | 56.5                     |
| 1/2" Uponor helioPEX X2, 300-ft. coil   | H1250500        | 19.7                       | 32                         | 4                 | 0.475                      | 0.625                      | 16.53                    |

| Nom de la pièce | Numéro de pièce | Les codes                            | Normes   | Annonces   |
|-----------------|-----------------|--------------------------------------|--|--|
| Heliopex X2     | All             | IRC NBC of Canada UFGS UMC USEHC IMC | ASTM F877 ASTM E814 ULC S115 ASTM F1960 ULC S102.2 CSA B137.5 CSA B214 ULC S101 ASTM E84 NSF/ANSI 14 | cNSFus-rfh CCMC PPI TR-4 ASTM E84/ULC S102.2 UL 2846 cQAIus P321 |

### L'installation

Approved fitting system is ProPEX®. Refer to the Uponor Radiant Floor Heating Installation Handbook for further information.

### Applications connexes

### Notes de bas de page

### Coordonnées de la personne-ressource

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517