

Coudes au quart ProPEX en cuivre en laiton sans plomb (LF)



Renseignements sur le projet

| | |
|-----------------------------|---------------------|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |


Données techniques

| | |
|-------------------------|--|
| Material | Copper |
| Subcomponent Material | LF Brass Copper |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |

Informations sur le produit et utilisation de l'application

The ProPEX® Copper Tub Ell, 1/2" PEX Lead-free (LF) Brass x 1/2" Copper is available for use in hot and cold domestic potable water systems.1 The copper tub ell is comprised of 1/2" copper pipe with an Uponor ProPEX Fitting on one end and the other end open

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Nom de la pièce | Numéro de pièce | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | End Type 1 | Weight per UOM [lbs/UOM] |
|--|-----------------|----------|----------|----------|----------|----------|----------|----------|-------------|--------------------------|
| ProPEX LF Copper Stub Ell, 1/2" PEX LF Brass x 1/2" Copper (3 1/2" x 8") | LF2865050 | 7.987 | 0.709 | 3.749 | 3.084 | 8.372 | 0.77 | 4.77 | ProPEX 1/2" | 0.2 |
| ProPEX LF Copper Tub Ell, 1/2" PEX LF Brass x 1/2" Copper (3" x 6") | LF2875050 | 2.989 | 0.709 | 5.279 | 1.542 | 3.374 | 0.77 | 6.3 | ProPEX 1/2" | 0.23 |
| ProPEX LF Copper Stub Ell, 1/2" PEX LF Brass x 1/2" Copper (13" x 8") | LF2855050 | 7.987 | 0.709 | 12.299 | 3.084 | 8.372 | 0.77 | 13.32 | ProPEX 1/2" | 0.5 |
| ProPEX LF Copper Tub Ell, 1/2" PEX LF Brass x 1/2" Copper (3" x 4") | LF2885050 | 2.989 | 0.709 | 3.279 | 1.542 | 3.374 | 0.77 | 4.3 | ProPEX 1/2" | 0.2 |
| ProPEX LF Copper Stub Ell, 1/2" PEX LF Brass x 1/2" Copper (8" x 13") | LF2895050 | 12.985 | 0.709 | 7.295 | 3.04 | 13.37 | 0.77 | 8.316 | ProPEX 1/2" | 0.48 |
| ProPEX LF Copper Stub Ell, 3/4" PEX LF Brass x 3/4" Copper (4" x 8") | LF2897575 | 8.002 | 0.945 | 4.057 | 3.959 | 8.552 | 1.1 | 5.44 | ProPEX 3/4" | 0.5 |
| ProPEX LF Copper Stub Ell, 1" PEX x 1" Copper (13" x 8") | LF2891010 | 13 | 1.181 | 6.507 | 8 | 13.68 | 1.36 | 8.25 | ProPEX 1" | 1.7 |

| Nom de la pièce | Numéro de pièce | Les codes | Normes | Annonces |
|--|-----------------|--|--|----------------------|
| Coudes au quart ProPEX en cuivre en laiton sans plomb (LF) | All | UPC IBC IRC IPC NPC of Canada UMC NSPC IMC | NSF/ANSI/CAN 372 ASTM F877 ASTM F1960 CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14 | IAPMO-ES HUD MR 1269 |

In addition, the following parts have additional codes, standards, or listings:

| | |
|--|-----------|
| ProPEX LF Copper Stub Ell, 1/2" PEX LF Brass x 1/2" Copper (3 1/2" x 8") | LF2865050 |
| ProPEX LF Copper Stub Ell, 1/2" PEX LF Brass x 1/2" Copper (8" x 13") | LF2895050 |
| ProPEX LF Copper Stub Ell, 3/4" PEX LF Brass x 3/4" Copper (4" x 8") | LF2897575 |
| ProPEX LF Copper Stub Ell, 1" PEX x 1" Copper (13" x 8") | LF2891010 |

L'installation

Use compression fitting with a male national pipe thread (MNPT) adapter. Refer to the AquaPEX® Professional Plumbing Installation Guide for additional information.

Applications connexes

- PEX-a Plumbing Systems
- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517
