

Trousses d'extension de tige de valve à bille commerciale ProPEX en laiton sans plomb (LF)



Renseignements sur le projet


Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material Galvanized steel

Informations sur le produit et utilisation de l'application

To help meet the stringent demands of commercial plumbing and hydronic distribution projects, Uponor is offering new ProPEX® ASTM F1960 lead-free (LF) brass ball valves in sizes from ½" to 2". The full-port ball valves feature a stainless-steel ball and stem for greater durability, longevity, and system performance.



Nom de la pièce	Numéro de pièce	A [inch]	B [inch]	C [inch]	D [inch]	Weight per UOM [lbs/UOM]
2 3/8" Stem Extension Kit for 1/2" and 3/4" LFCSS Ball Valves	F6630001	3.3	1.02	1.02	2.82	0.39
2 5/8" Stem Extension Kit for 1" and 1 1/4" LFCSS Ball Valves	F6630002	3.4	1.293	1.293	2.8	0.66
2 5/8" Stem Extension Kit for 1 1/2" and 2" LFCSS Ball Valves	F6630003	3.57	1.369	1.369	2.88	0.77

L'installation

Install valve and stem extension kit according to local building code. Do not dismantle. Refer to the Uponor Piping Pocket Guide or the Uponor Plumbing Design Assistance Manual (PDAM) for additional information.

Applications connexes

- Hot water distribution
- Hydronic heating and cooling systems
- Hydronic Piping Systems
- Hydronic Radiant Heating and Cooling Systems
- PEX-a Plumbing Systems
- Plumbing Systems
- Pre-Insulated Pipe Systems
- Radiant Heating and Cooling Systems

Notes de bas de page

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517