

Boîtiers pour machine à glaçons ProPEX en laiton sans plomb (LF) (en angle)



Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Informations sur le produit et utilisation de l'application

The ProPEX® Ice Maker Box with Support Brackets, 1/2" (LF Brass) Valve with snap-in frame includes a 1/2" lead-free brass valve with 1/4" O.D. compression connection. This high-impact box is an aesthetic, convenient option for connecting to standard ice maker tubing. Two support brackets are provided for easy mounting.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Nom de la pièce	Numéro de pièce	A [inch]	B [inch]	C [inch]	Material group	End Type 1	End Type 2	Prop 65 label required?	Weight per UOM [lbs/UOM]
ProPEX Ice Maker Box with Support Brackets, 1/2" LF Brass Valve	LF5955025	20.29	6	3.55	-	ProPEX	Compression	Yes	0.87
1/4" Insert (stainless steel)	F5400250	0.719	0.323	0.323	Stainless Steel	-	-	-	0

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Boîtiers pour machine à glaçons ProPEX en laiton sans plomb (LF) (en angle)	All	UPC IPC NPC of Canada	ASME A112.18.1 NSF/ANSI/CAN 372 ASTM F877 ASTM F1960 CSA B125 CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14	cNSFus-pw-G U.P.Code

L'installation	Applications connexes
Mount in wall cavity at the desired location (e.g., behind refrigerator) using the supplied mounting brackets or directly to studs. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide.	PEX-a Plumbing Systems

Notes de bas de page	Coordonnées de la personne-ressource	
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517