

Adaptateurs filetés mâles ProPEX en acier inoxydable

Renseignements sur le projet

| | |
|-----------------------------|---------------------|
| Nom du poste : | Lieu : |
| Ingénieur : | Date de soumission: |
| Entrepreneur : | Présentée par: |
| Représentant du fabricant : | Approuvé par : |

Données techniques

| | |
|-----------------------|--|
| Material | Stainless Steel |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |

Informations sur le produit et utilisation de l'application

ProPEX® Stainless Steel Male Threaded Adapters are available for use with reverse osmosis, deionization, and distillation applications producing conditioned water. 1 One end of the adapter is manufactured with the Uponor ProPEX Fitting for connections to Wirsbo AQUAPEX® tubing.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Nom de la pièce | Numéro de pièce | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | Cv | Equivalent length through [ft] | End Type 1 |
|---|-----------------|----------|----------|----------|----------|----------|----------|----------|------|--------------------------------|-------------|
| ProPEX Stainless-steel Male Threaded Adapter, 1/2" PEX x 1/2" NPT | Q8525050 | 1.67 | 0.961 | 1 | 0.427 | 0.709 | 0.875 | 0.5 | 5 | 2.26 | ProPEX 1/2" |
| ProPEX Stainless-steel Male Threaded Adapter, 3/4" PEX x 3/4" NPT | Q8527575 | 1.905 | 1.01 | 1.289 | 0.464 | 0.895 | 1.125 | 0.644 | 11.3 | 2.67 | ProPEX 3/4" |
| ProPEX Stainless-steel Male Threaded Adapter, 1" PEX x 1" NPT | Q8521010 | 2.32 | 1.139 | 1.578 | 0.456 | 1.181 | 1.375 | 0.789 | 19.9 | 0 | ProPEX 1" |

| Nom de la pièce | Numéro de pièce | End Type 2 | Weight per UOM [lbs/UOM] |
|---|-----------------|------------|--------------------------|
| ProPEX Stainless-steel Male Threaded Adapter, 1/2" PEX x 1/2" NPT | Q8525050 | MNPT 1/2" | 0.52 |
| ProPEX Stainless-steel Male Threaded Adapter, 3/4" PEX x 3/4" NPT | Q8527575 | MNPT 3/4" | 0.2 |
| ProPEX Stainless-steel Male Threaded Adapter, 1" PEX x 1" NPT | Q8521010 | MNPT 1" | 0 |

| Nom de la pièce | Numéro de pièce | Les codes | Normes | Annonces |
|--|-----------------|--|---------------------------------------|---|
| Adaptateurs filetés mâles ProPEX en acier inoxydable | All | UPC IBC IRC IPC NPC of Canada UMC NSPC JMC | ASTM F1960 CSA B137.5 NSF/ANSI/CAN 61 | HUD MR 1269 ICC-ES-PMG cNSFus-pw APMO 3558 U.P.Code |

| L'installation | Applications connexes |
|---|------------------------|
| Use the appropriate ProPEX Ring for the tubing. For more information, refer to the AQUAPEX Professional Plumbing Installation Handbook or Uponor Radiant Floor Installation Handbook. | PEX-a Plumbing Systems |

| Notes de bas de page | Coordonnées de la personne-ressource | | |
|---|--|---|---|
| - | <table border="0"> <tr> <td>Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008</td> <td>Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517</td> </tr> </table> | Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 | Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517 |
| Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 | Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517 | | |