

Collecteurs sans vanne en cuivre (type L)

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	Copper
End type 1	Sweat 3/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) 210 °F (99 °C) at 149 psi (10.3 bar)
Prop 65 label required?	Yes

Informations sur le produit et utilisation de l'application

Use the Uponor 2" Copper Valveless Manifold in hot and cold domestic potable water distribution systems or balanced radiant heating and/or cooling systems that do not require individual loop control. The manifold features 3/4" sweat connections



Nom de la pièce	Numéro de pièce	A [Inch]	B [Inch]	C [Inch]	Manifold Body Size (I.D.) [Inch]	Flow Rate Max. [gpm]	Weight per UOM [lbs/UOM]
2" x 6' Copper Valveless Manifold with 24 outlets, 3/4" sweat	F2802075	72	4.125	2.125	2	45	12.35
1 1/2" x 6' Copper Valveless Manifold with 24 outlets, 3/4" sweat	F2801575	72	3.625	1.625	1.5	21	8.7

Nom de la pièce	Numéro de pièce	Les codes	Normes	Annonces
Collecteurs sans vanne en cuivre (type L)	All	UPC IPC NPC of Canada NSPC	CSA B137.5 ASTM F877	NSF 14- and 61-certified

L'installation

Use any product designed to mount 2" copper pipe as a mounting bracket. Any bend within 6 inches of the connection to the manifold requires the use of a tube talon (F7050750) or bend supports (A5110750 or A5150750)

Applications connexes

PEX-a Plumbing Systems
Radiant Heating and Cooling Systems

Notes de bas de page

Coordonnées de la personne-ressource

-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	---	---