

Joist Trak

Renseignements sur le projet

Nom du poste :	Lieu :
Ingénieur :	Date de soumission:
Entrepreneur :	Présentée par:
Représentant du fabricant :	Approuvé par :

Données techniques

Material	Aluminum
Subcomponent Material	16-gauge aluminum
Prop 65 label required?	Yes

Informations sur le produit et utilisation de l'application

Use Joist Trak™ extruded aluminum heat transfer panels with $\frac{3}{8}$ " or $\frac{1}{2}$ " Uponor PEX in floor joist applications. Each panel is 4 feet long by $3\frac{1}{2}$ inches wide, and comes packaged 20 per box. It provides easy installation, increased heat transfer and superior comfort.



Nom de la pièce	Numéro de pièce	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
Joist Trak, 3/8" Heat Transfer Panel	A5080375	48	3.5	0.546	-
Joist Trak, 1/2" Heat Transfer Panel	A5080500	48	3.5	0.675	-

L'installation

Using the pre-punched mounting holes, install the panels with either screws or nails. Leave a minimum $\frac{1}{4}$ " gap between plates to allow for expansion. Simply snap the tubing into the channel of the Joist Trak panel. Refer to the Uponor Joist Trak Heat Transfer Panel Installation Handbook for additional information.

Applications connexes

Radiant Heating and Cooling Systems

Notes de bas de page

Coordonnées de la personne-ressource

-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	---	---