

Tapis à rayonnement Rollout

Renseignements sur le projet

Nom du poste :

Lieu :

Ingénieur :

Date de
soumission:

Entrepreneur :

Présentée par:

Représentant du fabricant :

Approuvé par :

Informations sur le produit et utilisation de l'application

The Radiant Rollout™ Mat features 1/2" or 5/8" Wirsbo hePEX™ tubing that has an oxygen-diffusion barrier that meets German DIN 4726/9. The mat can include a 3/4" reverse-return header with 3/4" ProPEX EP fittings that is pressurized to 20 psi to ensure system integrity. The mat can also be designed without a reverse-return header. In this instance, it is not prepressurized and can connect to a wall manifold such as the TruFLOW™ Classic Manifold



L'installation

At the jobsite, roll out the mat and, depending on your header/manifold selection, connect to a supply-and-return line using the attached header (optional) or connect each loop to a wall manifold (optional). Contact your local Uponor representative for more information.

Applications connexes

Radiant Heating and Cooling Systems
Permafrost Protection Systems
Turf Conditioning Systems

Notes de bas de page

-

Coordonnées de la personne-ressource

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517