

DECLARATION OF PERFORMANCE

CPR-5-IWW-1000005

1. Unique identification code of the product-type:

Infiltration Septic Tank 2,4 m³ gravity, product number 1084646

Infiltration Septic Tank 2,4 m³ with pump, product number 1084647

Infiltration Septic Tank 2,4 m³ with pump and riser, product number 1084648

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

n/a

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Prefabricated septic tank

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Uponor Infra AB, SE 513 81 Fristad, Sweden

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Uponor Infra Oy, FIN-15561 Nastola, Finland

Uponor Infra A/S. DK-5500 Middelfart, Denmark

Uponor Infra AS, N-1540 Vestby, Norway

Uponor Infra AS, 13811 Tallinn, Estonia

Uponor Latvia SIA, LV-1045 Riga, Latvia

Uponor UAB, LT-06115 Vilnius, Lithuania

CJSC Uponor Infra, 127287, Moscow, Russia

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 12566-1: 2016

SP, Box 857, 50115 Borås, Sweden, Notified Body No. 0402 and VTT Expert Services Oy, Notified Body No. 0809 performed the initial type testing of product under system 3 and issued following test reports:


SP 5P04257

VTT:VTT-S-03211-15

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

n/a

9. Declared performance

		
Essential characteristics	Performance	Harmonised technical specification
Hydraulic efficiency	Gravity: 0,35 g of beads With pump: 3,50 g of beads	EN 12566-1:2016
Nominal capacity	Gravity: 2,4 m ³ With pump: 2,0 m ³	
Watertightness	Pass	
Crushing resistance	Pass	
Durability	Pass	
Reaction to fire	NPD	
Release of dangerous substance	NDP	

- 10. The performance of the product identified in point 1 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by:



Niila Tast
Application Manager IWW
Date: 08-03-2019