

Supply water temperature charts

Concrete — 4" slab (12" on center)




Concrete — 4" slab (9" on center)




Supply water temperature charts

Concrete — 4" slab (6" on center)





11/2" Poured floor underlayment (12" on center)




Supply water temperature charts

1½" Poured floor underlayment (9" on center)





11/2" Poured floor underlayment (6" on center)




Supply water temperature charts

Joist heating — no plates (8" on center)

65°F Room setpoint temperature

Floor covering R-value (R_v)

This temperature chart has already factored in the R-value for a ¾-inch plywood subfloor.



Note: The maximum fluid temperature for all joist applications is 180°F.
Uponor's recommended maximum design temperature is 165°F. This data assumes negligible downward loss in accordance with good insulation practices.

 $R_{v} = 0.5$

 $R_v = 1.0$ $R_v = 1.5$ $R_v = 2.0$

 $R_{v}^{*} = 2.5$ $R_{v} = 3.0$

 $R_{v} = 0.5$


 $R_{v}^{*} = 2.0$ $R_{v} = 2.5$ $R_{v} = 3.0$

Joist heating — double-groove aluminum plates (8" on center)

65°F Room setpoint temperature

Floor covering R-value (R_v)

This temperature chart has already factored in the R-value for a ¾-inch plywood subfloor.



Note: The maximum fluid temperature for all joist applications is 180°F. Uponor's recommended maximum design temperature is 165°F. This data assumes negligible downward loss in accordance with good insulation practices.


Supply water temperature charts

Joist heating — Joist Trak™ (8" on center)

65°F Room setpoint temperature

Floor covering R-value (R_v)

This temperature chart has already factored in the R-value for a ¾-inch plywood subfloor.




Radiant ceiling — Joist Trak (8" on center)

65°F Room setpoint temperature

Floor covering R-value (R_v)

This temperature chart has already factored in the R-value for a ¾-inch plywood subfloor.




Supply water temperature charts

Quik Trak® radiant floor (7" on center)

65°F Room setpoint temperature

Floor covering R_v



Note: Uponor's recommended maximum design temperature is 165°F.



