

Uponor Wipex draadflens binnendraad F32/4-100/G1 1/4


1018360

- Cilindrische G-binnendraad met O-ring
- Maximaal +95 °C / 10 bar of +20 °C / 16 bar
- KOMO systeemcertificering
- Kiwa systeemcertificering
- Verklaring volgens DIN EN 15632
- DVGW-W534
- ÖVGW PW302



Uponor Wipex draadflens binnendraad F32/4-100/G1 1/4

1018360



Technische gegevens

Item no EAN	7331541099301
Item no GTIN	07331541099301
Item no VVS	087844032
RSK no.	2410646
Item no NRF	8360752
Item no LVI	1938132
Item maateenheid	st.
Z-meting K	100 mm
Hoeveelheid verpakking 1	1
Hoeveelheid verpakking 3	5
Hoeveelheid verpakking 4	240
Packaging GTIN PL1	06414905437900
Packaging GTIN PL3	06414905446728
Packaging GTIN PL4	06414905490714
Item Unit Length	140
Item Unit Height	28
Item Unit Weight	1,959
Item Unit Width	140

Uponor GmbH

Industriestraße 56
97437, Haßfurt
Duitsland

T +49 (0)9521 690-0
E info.nl@uponor.com
F +49 (0)9521 690-231

www.uponor.com/nl-nl