

Uponor Wipex draadflens binnendraad F80/8-160/G3

1018364

- Cilindrische G-binnendraad met O-ring
- Maximaal +95 °C / 10 bar of +20 °C / 16 bar
- KOMO systeemcertificering
- Kiwa systeemcertificering
- Verklaring volgens DIN EN 15632
- DVGW-W534
- ÖVGW PW302



Uponor Wipex draadflens binnendraad F80/8-160/G3

1018364



Technische gegevens

| | |
|--------------------------|----------------|
| Item no EAN | 7331541099349 |
| Item no GTIN | 07331541099349 |
| Item no VVS | 087844080 |
| RSK no. | 2410650 |
| Item no NRF | 8360756 |
| Item no LVI | 1938180 |
| Item maateenheid | st. |
| Z-meting K | 160 mm |
| Hoeveelheid verpakking 1 | 1 |
| Hoeveelheid verpakking 3 | 3 |
| Packaging GTIN PL1 | 06414905437948 |
| Packaging GTIN PL3 | 06414905446766 |
| Item Unit Length | 200 |
| Item Unit Height | 28 |
| Item Unit Weight | 4,183 |
| Item Unit Width | 200 |

Uponor GmbH

Industriestraße 56
97437, Haßfurt
Duitsland

T +49 (0)9521 690-0
E info.nl@uponor.com
F +49 (0)9521 690-231

www.uponor.com/nl-nl